

# R&D Activities for Neutrino Beam in Asia

---

Yoshitaka Kuno  
Department of Physics  
Osaka University

October 23rd, 2010  
NuFACT10 Workshop  
Tata Institute of Fundamental Research, Mumbai, India

# Outline

---





- Conventional Super Neutrino Beam
- Neutrino Beam based on Muon decays
  - Study on Muon Acceleration
  - Demonstration of a Highly Intense Muon Source
- Summary

Conventional  
Super Neutrino Beam

# T2K Future Plan

from Prof. Takashi Kobayashi

# Neutrino Beam in Japan - T2K



**J-PARC Facility  
(KEK/JAEA)**

**Linac**

**3 GeV  
Synchrotron**

**Neutrino Beams  
(to Kamioka)**

**Materials and Life  
Experimental  
Facility**


**Main Ring  
Synchrotron**

**Slow-extra.  
Experimental  
Facility**

- CY2007 Beams**
- JFY2008 Beams**
- JFY2009 Beams**

Bird's eye photo in January of 2008

# Short-term Scenario of Beam Power Improvement at J-PARC Main Ring



studies and R&D on power supply, RF configuration, etc. are being made.

# Long-term Scenario for MW Beam Power Improvement at J-PARC

	Day1 <b>Achieved !</b> (up to Jul.2010)	Next Step	KEK Roadmap
Power(MW)	0.1	0.45	>1.66
Energy(GeV)	30	30	30
Rep Cycle(sec)	3.5	2.2	1.92~0.5
No. of Bunch	6	8	8
Particle/Bunch	$1.2 \times 10^{13}$	$2.5 \times 10^{13}$	$4.1 \sim 8.3 \times 10^{13}$
Particle/Ring	$7.2 \times 10^{13}$	$2.0 \times 10^{14}$	$3.3 \sim 6.7 \times 10^{14}$
LINAC(MeV)	181	181	400
RCS	h=2	h=2	h=2 or 1

by combination of high rep. cycle and high beam density


## T2K Beamline for a MW beam

---


According to Prof. Takashi Kobayashi (KEK), major upgrade of the T2K beamline may **not** be needed for a beam power up to about 2 MW.

# Neutrino Beam - Angle and Baseline

- Off-axis angle
    - On-Axis: Wide Energy Coverage,
      - Energy Spectrum Measurement
      - × Control of  $\pi^0$  Background
    - Off-Axis: Narrow Energy Coverage,
      - Control of  $\pi^0$  Background
      - × Energy Spectrum Measurement
- Counting Experiment



- Baseline
  - Long:
    - 2<sup>nd</sup> Osc. Max. at Measurable Energy
    - × Less Statistics
    - ? Large Matter Effect
  - Short:
    - High Statistics
    - × 2<sup>nd</sup> Osc. Max. Too Low Energy to Measure
    - ? Less Matter Effect



# Three Future Scenario of Long Baseline Neutrino Oscillation Program at J-PARC

## Three Possible Scenario



NP08 is **The 4th International Workshop on Nuclear and Particle Physics at J-PARC**



<http://j-parc.jp/NP08>

Scenario 1

# *J-PARC to Okinoshima*

P32 proposal (Lar TPC R&D)  
Recommended by J-PARC PAC  
(Jan 2010), arXiv:0804.2111

Distance = 658 km  
Off-axis angle =  $0.76^\circ$   
( $2.5^\circ$  @ SK)  
100 kton liquid Argon



→ Extract  $\delta_{CP}$  from fit of 1<sup>st</sup> & 2<sup>nd</sup> maximum

# J-PARC to Okinoshima:

## CP Violation

## Sensitivities





Fig. 9: Discovery potential for CP-violation at 90%C.L. and 3σ for (top) 1 resp. 5 years 1+1 resp. 5+5 years neutrino-antineutrino runs.

## Hierarchy

Mass Hierarchy Determination - 1.6MW - 100 kton




Fig. 10: Mass hierarchy discrimination at 90%C.L. and 3σ for 5+5 years neutrino-antineutrino runs.

# J-PARC-Okinoshima feasibility studies

(Some examples)

Site visit



### Okinoshima: Geology and Geography

**ASAHI quarry**

Islands were born by volcanic activity in 5~6M years ago.

**TOKUHATA No.2 quarry**

BUT, bedrock is the oldest rock in Japan (2G years), which has been left as → **OKI-Gneiss**

**Suitable for Big Cavern Construction**

There are several quarries, good for direct observation of geology.

### ASAHI quarry

A single layer of the gneiss

### Okinoshima. Geology and Geography

**A conceptual design**

**Site No.1**

ASAHI Quarry

E.L.367

252m


E.L.65.0

E.L.63.0

Access Tunnel 3 L=760m

Shallow depth (>600 m.w.e.) is enough to suppress cosmogenic background (A. Bueno et al., JHEP 0704,041 (2007))

If more overburden is necessary, inclined access tunnel is also possible



PENTA-OCEAN construction co., Ltd.,

### Potential LiqAr supply

Liquid Argon production bases in CHUGOKU/KYUSHU area

~100km

**OKINOSHIMA**

Sufficient production rate of Liquid Argon to procure 100 kton detector





SYUUNAN CITY SYUUNAN SANSO	510 liter/h
YAHATA CITY SHINNITTETSU	3,684 liter/h
HIKARI CITY SHINNITTETSU	77 liter/h
KURE CITY NISSHIN SANSO	1,620 liter/h
KURASHIKI CITY MIZUSHIMA OKISHITON	383 liter/h
TM AIR	128 liter/h
JFE STEEL	1,275 liter/h
FUKUYAMA CITY JFE-SANSO CENTRE	2,270 liter/h

# Scenario 2: J-PARC-HyperK @ Kamioka

item	parameters	Shiozawa, Nu2010
$\nu$ beam	Quasi-monochromatic beam (off-axis 2.5 degree, $E_\nu \sim 0.6\text{GeV}$ ) Upgraded to <b>1.66MW</b>	
Far $\nu$ detector	<b>0.54Megaton</b>	
Data taking period	<b>5 yrs</b> (1.1 yrs $\nu$ mode + 3.9 yrs anti- $\nu$ mode) – <b>10yrs</b> *1 yrs = $10^7$ sec	
Electron selection	Single-Ring, $P_e > 100\text{MeV}/c$ , no decay-e, $M_{\pi^0} < 100\text{MeV}/c^2$ , $\cos\theta_\mu < 0.9$	
systematic errors (reference)	<b>5%</b> for $\nu e$ signal, NC BG, beam $\nu e$ (anti- $\nu e$ ), $\nu$ mode/anti- $\nu$ mode normalization	
$\nu$ parameters	$\sin^2\theta_{23}=0.5$ , $\Delta m^2_{23}=2.4 \times 10^{-3}\text{eV}^2$ (normal hierarchy), $\sin^2\theta_{12}=0.32$ , $\Delta m^2_{12}=7.6 \times 10^{-5}\text{eV}^2$	

**$N_e(\delta)$  = selected electron signal**


**$N_e(\delta)$  ( $N_e(\delta=0)$  subtracted)**



# Scenario 2: J-PARC-HyperK @ Kamioka

Shiozawa, Nu2010


HK 0.54Mt, 1.66MW, 1.1/3.9 yrs



# Hyper-K feasibility studies

Shiozawa, Nu2010

## Schematic View of the Hyper-Kamiokande



## Site studies so far


- ✓ site selection (Tochibora mine, +480-550m s.l.)
- ✓ geological sketching – very sound intact mass in excellent condition
- ✓ core boring – geological map, joint orientation survey
- ✓ rock sampling – mechanical property of rock mass and joint
- ✓ initial state of stress in the rock mass
- ✓ conceptual design of cavern and layout (two 250m tunnels with 100m spacing)
- ✓ FEM analysis of the cavern
- ✓ clean natural water supply



Initial state of stress in the rock mass (important for cavern design)





Diamond Drilling




mechanical properties of rock mass as well as joint measurements

# Scenario 3


- Cover 2<sup>nd</sup> Maximum @ Korea
- Cover 1<sup>st</sup> Maximum @ Kamioka
- 5 Years  $\nu$ +5 Years  $\bar{\nu}$  Run 1.66MW
- 270kt Water Cherenkov Detector each @ Korea, Kamioka



Spectrum at Kamioka



Spectrum at Korea 1.0° OA



$\sin^2(2\theta_{13})=0.04$ , neutrino, normal hierarchy, Scenario B

F.Dufour@NP08

(study is initiated by M.Ishitsuka et. al. hep-ph/0504026)

Neutrino Beam  
based on Muon Decays

# FFAG Muon Acceleration

from Prof. Y. Mori's talk  
pl. visit J.B. Lagrange on Sunday

# ADVANTAGES OF SCALING FFAG FOR MUON ACCELERATION

- Free from resonance crossing. Large transverse acceptance can be realized.
- Free from longitudinal emittance degradation caused by path-length(time-of-flight) difference for large emittance beam.
- Numbers of RF cavities can be less compared with RLA. Construction cost can be reduced.

# DESIGN STUDY OF ADVANCED SCALING FFAG FOR MUON ACCELERATION

- Required specifications

- Energy range 3.6 - 12.6 GeV

- Acceptance

- horizontal  $> 30\pi$  mm.rad

- longitudinal  $> 150$ mm

- RF frequency for acceleration 200MHz

- To accelerate simultaneously  $\mu^+$  and  $\mu^-$

# DESIGN OF SCALING FFAG

## ACCELERATION INSIDE OF RF STATIONARY BUCKET

**Principle:** use the synchrotron motion to accelerate beam going from the low energy to the high energy part of a stationary rf bucket.

**Case of scaling FFAGs:** since the momentum compaction is constant with energy, the longitudinal dynamics can be analytically described without

assuming  $\frac{\Delta p}{p}$  small<sup>(\*)</sup>.

<sup>(\*)</sup> see E.Yamakawa and Y.Mori's paper to appear in proceedings of FFAG'09 conference.




Figure 1 - Longitudinal phase space showing the acceleration of a muon beam (red) inside the stationary rf bucket of a scaling FFAG ring. Hamiltonian contour are shown in black.

# CHOICE OF WORKING POINT

Emittance scan in the case of a ring made of 225 identical FDF triplet FFAG cells. Legends in the top left corner of each diagram give values of acceptances normalized in the case of 3.6 GeV muons. Normal structure resonances lines, plotted up to the octupole, are superimposed.




Figure 2a - Horizontal acceptance scan.

Figure 2b - Vertical acceptance scan.

# PARAMETERS OF A 3.6 - 12.6 GEV MUON RING

Lattice type	FDF triplet
Injection/extraction energy	3.6/12.6 GeV
RF frequency	200 MHz
Number of turns	6
RF peak voltage (per turn)	1.8 GV
Synchronous energy	8.04 GeV
Mean radius	$\sim 160.9$ m
$B_{max}$ (@ 12.6 GeV)	3.9 T
Field index $k$	1390
Total orbit excursion	14.3 cm
Harmonic number $h$	675
Number of cells	225
Long drift length	$\sim 1.5$ m
Horiz. phase adv. per cell	85.86 deg.
Vert. phase adv. per cell	33.81 deg.






Table I - Example of 3.6 to 12.6 GeV muon scaling  
FFAG ring parameters.


Figure 3 - Ring layout.

# FULL ACCELERATION CYCLE 6D TRACKING

- Tracking results -



Figures 8 - Initial (blue) and final (red) particles distribution in the horizontal (top), and vertical (bottom) phase space.



Figures 9 - longitudinal phase space plot showing a 6-turn acceleration cycle. Hamiltonian contours are superimposed.

R&D on a Highly Intense Muon Source  
- MuSIC@Osaka -

a la Akira Sato's talk (22nd)

# Production and Collection of Pions and Muons

## Conventional muon beam line

**J-PARC**  
**MUSE**  
**proton beam**

-1000kW

**target**

graphite  
t20mm  
 $\phi$ 70mm

**proton beam**

**Capture magnets**

SuperOmega  
 $\Omega$ :400mSr

**muons**

proton beam loss  
< 5%

**to the neutron facility**

## Much efficient

**MuSIC**

**proton beam**

-0.4kW

**target**

graphite  
t200mm  
 $\phi$ 40mm

**proton beam**

**muons**

**Transport solenoid**

**Capture solenoid**

Collect pions and muons  
by 3.5T solenoidal field


**to a beam dump**

MuSIC, COMET, PRISM,  
Neutrino factory,  
Muon collider


**Large solid angle & thick target**

# Pion Capture System in MuSIC, COMET, and NuFact


## MuSIC



## COMET




## Neutrino Factory



# MuSIC at RCNP, Osaka University

Research Center for Nuclear Physics (RCNP), Osaka University has a cyclotron of 400 MeV with 1 microA. The energy is above pion threshold.



# Muon Science in Japan

## DC muon


Muon Facility  
MuSIC  
(Osaka)

400W  
CW  
 $10^8$  /sec  
single channel

## Pulsed muon

Muon Facility  
MUSE  
(J-PARC)

1000kW  
pulsed (25 Hz)  
 $10^8$  /sec  
many channels



Japan will be the only country which has both  
DC and pulsed muon beam facilities.



# MUSIC Specification

---

	MUSIC
location	RCNP
beam power	0.4 kW
intensity	$10^8$ - $10^9$ /sec
time structure	continuous
beam momentum	20 - 140 MeV/c
beam polarization	medium (at full intensity)



# Muon Physics Programs at MUSIC

---

- **Particle Physics** :
  - search for  $\mu \rightarrow eee$  (muon LFV)
    - DC continuous beam is critical
    - TPC to track 3 electrons/positrons
- **Nuclear Physics** :
  - nuclear muon capture (NMC)
  - pion capture and scattering
- **Materials Science** :
  - $\mu$ SR (a  $\mu$ SR apparatus is needed)
- **Chemistry**
  - chemistry on pion/muon atoms
- **Accelerator / Instruments R&D** (for neutrino factory/muon collider)
  - Superconducting solenoid magnets
  - FFAG, RF
  - cooling methods

Demonstration of  
COMET muon beam


# MuSIC (=MUon Science Innovative Commission)

## muon yield estimation

*proton beam 0.4 kW (400MeV, 1 $\mu$ A)*

*10<sup>8-9</sup> muons/sec*


Nuclear and particle physics,  
material science  
chemistry, and accelerator R&Ds  
will be possible.



A final layout plan of the MuSIC in the W-hall, RCNP, Osaka Univ.


# Construction Status and Schedule

The construction has started at 2009, and will be finished in 5 years.




# Construction Status and Schedule

The construction has started at 2009, and will be finished in 5 years.




# Construction Status and Schedule

The construction has started at 2009, and will be finished in 5 years.



# MuSIC in 2010






# Pion Capture System and Pion/Muon Transport System

## Pion Capture System

- solenoid magnetic field : 3.5 T
- cryocooler cooling
- graphite target


## GM Cryocooler 2x1.5W+1W




## Pion Transport System

- solenoid magnetic field : 2 T
- (5+3) solenoid coils
- dipole correction coil (for momentum selection)
- cryocooler cooling

# MuSIC






# Requirements to the superconducting solenoids

---

- Strong magnetic field on the pion production target
  - Trap pions in 3.5 T
    - Superconducting coils surrounding the target
- Long solenoid transport channel with a big aperture
  - Pions decay out and muons transported in 2T solenoid
  - ~10m long
  - 360mm dia. bore
  - Correction dipole field for momentum and charge selection
- LHe free refrigeration
  - Conduction cooling by GM cryocoolers
    - Heat deposit on the coils < 1W
    - Dose < 1MGy
      - for insulator, glue ...
  - Neutron flux <  $10^{20}$ n/m<sup>2</sup>
    - avoid degradation of the stabilizer of SC wires



# Pion capture solenoid: radiation issue

- Radiation shields (27cm thick stainless steels) are installed b/w the target and the coils.
- MC simulation by MARS (M.Yoshida)
  - **Heat deposit: 0.6W**
    - 0.4W in the coils (~1ton)
    - 0.2W in the coil supports
  - **Dose on the coils < 10kGy/year**
  - **Heat load**
    - **100W** on the target
    - **50W** on the rad. shields
  - **Neutron flux:  $5 \times 10^{18} \text{n/m}^2/\text{year}$** 
    - no degradation is expected



# Pion capture solenoid: parameters

Conductor	Cu-stabilized NbTi
Cable diameter	$\phi 1.2\text{mm}$
Cu/NbTi ratio	4
RRR (R293K/R10K at 0T)	230-300
Operation current	145A
Max field on axis	3.5T
Bore	$\phi 900\text{mm}$
Length	1000mm
Inductance	400H
Stored energy	5MJ
Quench back heater Cu wire	1.2mm dia. ~1 $\Omega$ @4K





# Transport solenoids

The world first working beam line which adopts  $\cos\theta$  winding dipole coils


## Solenoid coils

Operation current	145A
Field on axis	2T
Bore	$\phi 480\text{mm}$
Length	200mm x8Coils
Inductance	124H
Stored energy	1.4MJ
Quench back heater Cu wire	1.3mm dia. ~0.05 $\Omega$ /Coil@4K




## Correction dipole coils

Coil layout	Saddle shape dipole
	6 layers
	528 turns (1 set)
Current	115A (Bipolar)
Field	0.04T
Aperture	$\phi 460\text{mm}$
Length	200mm
Inductance	0.04H/Coil
Stored Energy	280J/Coil







# Refrigeration

- **Conduction cooling by GM cryocoolers**
- Can be cooled down within 1 week with pre-cooling by LN2
  
- Pion capture solenoid
  - 4K: 1W+nucl. heating 0.6W
  - 300K→40K: 50W
    - GM 1<sup>st</sup> stage
  - 3 x GM cryocooler
    - 1.5Wx2+1Wx1 @4K
    - 45Wx2+44W @40K
- Transport solenoid
  - 4K: 0.8W
  - 300K→40K : 50W
    - GM 1<sup>st</sup> stage
  - 2 x Cryocoolers on each cryostat (BT5,BT3)
    - 1Wx2 @4K
    - 44Wx2 @40K
- Achievable temperature
  - Pion capture solenoid : 3.7K
  - Transport solenoids : 4.2K-4.5K(BT3), 4.5K-5.8K(BT5)




# Expected Muon Yield

- MC simulations were performed from the production target to the end of the transport solenoid (180ded.)
  - by Dr. M.Yoshida
- **Simulation codes:**
  - Hadron production at the graphite target
    - MARS
  - Tracking in the magnetic field
    - g4beamline




# Simulation results for $B_y = \pm 0.04\text{T}$

This is just an example. We need to optimize the beam characteristic for various experiments using collimators, DC separators, and so on.



$8 \times 10^8 \mu^+/\text{sec}$   
for 400MeV,  $1 \mu\text{A}$  proton beam



$2 \times 10^8 \mu^-/\text{sec}$   
for 400MeV,  $1 \mu\text{A}$  proton beam

- At the end of the transport solenoid (180 deg.)
- Charge of the muons can be selected by changing the direction of the dipole field.

# Charged Particle Trajectory in Curved Solenoids

- A center of helical trajectory of charged particles in a curved solenoidal field is drifted by

$$D = \frac{p}{qB} \theta_{bend} \frac{1}{2} \left( \cos \theta + \frac{1}{\cos \theta} \right)$$

$D$  : drift distance

$B$  : Solenoid field

$\theta_{bend}$  : Bending angle of the solenoid channel

$p$  : Momentum of the particle

$q$  : Charge of the particle

$\theta$  :  $\text{atan}(P_T/P_L)$

- This effect can be used for charge and momentum selection.

- This drift can be compensated by an auxiliary dipole field parallel to the drift direction given by


$$B_{comp} = \frac{p}{qr} \frac{1}{2} \left( \cos \theta + \frac{1}{\cos \theta} \right)$$

$p$  : Momentum of the particle



$q$  : Charge of the particle

$r$  : Major radius of the solenoid

$\theta$  :  $\text{atan}(P_T/P_L)$




# Momentum vs Dipole field $B_y$



# MuSIC First Beam from 29th and 30th, July, 2010

- A 36 hour beam time with 1 nA
- Measurements on
  - beam intensity and
  - beam spatial distribution
- Analysis is still being made.
- Preliminary results (right)
  - vertical beam distribution
  - **integrated rate:  $6 \times 10^8$  Hz/ $\mu$ A**
  - some corrections further needed to get final numbers.
- Future works
  - particle ID
    - mixture of pions, muons and electrons
  - momentum distribution
  - dipole field correction

counting rates as a function of vertical position



# Summary



---

- Future plans of the T2K upgrade are discussed. There are three scenarios.
- For neutrino beam based on muon decays, muon acceleration by scaling FFAGs is studied.
- R&D of a highly intense muon source at Osaka University (the MuSIC project) is going on. A muon intensity of  $10^8$  /sec is expected.
-

Backup






# G4Beamline Simulation on Muon Yields



muon yield estimation  
50 kW : 10<sup>11</sup> muons/sec  
(for COMET)  
0.4 kW : 10<sup>9</sup> muons/sec  
(for MUSIC)

8x10<sup>8</sup> μ<sup>+</sup>/sec






2x10<sup>8</sup> μ<sup>-</sup>/sec





# Muon Beam Profile at MUSIC

## Muon profile








# Muon Momentum Selection by Dipole Fields

By: dipole field

## Momentum selection




muon	
Entries	329
Mean	28.85
RMS	8.052
Underflow	0
Overflow	0
Integral	329






# Cooling of the superconducting solenoids (1)







# The West Experimental Hall and the MUSIC





# Restriction

---

- When a proton beam is on for nuclear experiments with the Grand Raiden spectrometer, we cannot enter the West experimental hall.
- Most of the beam times in May, June and July are reserved for such experiments using the Grand Raiden spectrometer.
- And therefore our access to the MUSIC is limited (for maintenance days or when the beam is on for the west experimental hall.)



# Things to do for the MUSIC commissioning

---

- Construction of scintillation counters for
  - beam intensity measurement
    - plastic scintillators
  - beam profile measurement
    - hodoscope or fiber-grooved counters with MPPC
  - beam particle identification (muon/pion/proton/electron)
    - X-ray measurements
    - range ?
- DAQ
  - not decided
- Monte Carlo simulation (GEANT4) on beam optics
  - collimator design in the beamline
  - eliminate beam backgrounds (electrons, protons, neutrons)

